



Single Family Residential Addition

How to Use this Guide

Provide three sets of plans and complete the following:


1. Complete this Building Guide by filling in the blanks on page two, and indicating which construction details will be used, and the R value of insulation used.

2. Provide 3 Plot Plans (site plan) showing dimensions of your project or addition and its relationship to existing buildings or structures on the property. Show all easements and the distance to existing property lines drawn to scale.

3. Provide three floor plans drawn to scale. See page 4.

4. Fill out a building permit application.

The majority of permit applications are processed with little delay. The submitted documents will help determine if the project is in compliance with building safety codes, zoning ordinances and other applicable laws.



Single Family Residential Addition

2x ___ rafters spaced ___" O.C. or
 Manufactured Trusses spaced ___" O.C.
(example: 2 x 12 Rafters Spaced 24" O.C.)

Sheathing _____
(example: 1/2" exterior plywood)

Minimum 1x ___ ridge board
(example: 1 x 12)

Roof covering _____
(example: Class A 3 tab shingles)

Note: For roofs with slopes less than 4:12, follow manufacturer's instructions for low slope application of roofing material.

12
pitch

Underlayment _____
(example: 1 layer t5# felt)

Ceiling Insulation _____
(example: P-18)

Wall Insulation _____
(example: R-19 Fiberglass Batts)

2x ___ ceiling joists @ ___ O.C.
(example: 2 x 8 @ 24" O.C.)

Donfile 2x ___ top plate
(example: 2 x 6)

5pan _____
(example: 23' 5")

Ceiling height _____
(example: 8')

Siding _____
(example: lap or T-111)

Wall sheathing _____
(example: 1/2" exterior plywood)

2x studs 4 O.C.

Cont. 2x ___ sift plate
(example: 2 x 4)

2x joists 4 O.C.
(example: 2x10 @ 24" O.C.)

Wall width _____
(example: 8")

rooting size ___" x ___"
example: 8" x 6"

Note: Attic ventilation and access may be required

Provide roof tie downs
 Solid 2x blocking between rafters that are 2x12 or greater

Note: Pre-engineered roof trusses w/truss clips may be used in lieu of roof structure shown.

Diagonal wind bracing or braced wall panels @ corners and each 25' of wall.

Note: Pre-engineered floor systems may be used and should be installed according to the manufacturer's installation instructions.

Access required

18" minimum from the interior grade level to the bottom of the top joists.

Engineered Design: Passions may be required if your site has swelling soil. A foundation designed by a Pennsylvania licensed architect or engineer may be required.

Check one
 Foundation: Engineered Design
 Foundation: Detail A
(see page 6)

Property Address:

Single Family Residential Addition

Heads Up

Site Plan

1. When drawing your plot plan be sure to show the location of electric, gas, sewer and water service lines. PA One Call (1-800-242-1776) shall be notified of the excavation to eliminate potential conflicts with *underground* utilities. The PA One Call certification number shall be retained for reference.

2. Show where the existing electric and gas meters are located on your home. These meters may have to be relocated and it is best to know this before you start construction.

Floor Plan

1. Smoke Alarms are required in new and existing bedrooms. Battery operated devices are acceptable.

2. Additions not to enclose bedroom or basement egress windows.

3. Safety glass is required at specific locations. When you draw the location of the new windows on the floor plan, the plan reviewer can identify which ones require safety glass.

4. Heat is required in all habitable rooms. Show how the addition will be heated on the plan.


Electric Code

Existing electric service may require an upgrade or relocation. Indicate the size of your electric service (the number on the main breaker) on your plan. This can help the plan reviewer if an upgrade is needed before you start construction.

Roof Overframe

When constructing a new valley, use a continuous board under the bottom cut of the new rafters to provide a solid nailing surface. The board should be at least 12" thick, nominal and should be at least as wide as the base of the new rafter.

Crawlspace Foundation Detail A



Sample Floor Plan

NOTES:

- A. New 3'-0" x 6'-8" door in existing wall
- B. Existing door removed, opening covered with drywall both sides
- C. New 5'-0" x 4'-0" cased opening (replaces existing window)
- D. New patio door with tempered glass
- E. New 6'-4" wide 4'-8" casement windows

Example: (2) 2"x10" headers at new window and door openings

